



### MATERIAL SAFETY DATA SHEET

Print date: 14-Apr-2016 Revision Number: 1 Revision date: 14-Apr-2016

### 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trade Name: LEXAN\* Sheet

**Product ID:** HF1110 HF1110R HF1130 HF1130R HFD1014 HFD1034 HFD1232 HP1

HFD4413 HFD4471 HFD4472 HFR1723 HFR1724 HPX LS1 LS2 HP2 LGK3020 LUX1169 LGK5030 LUX2180T LUX7189 LUX9610 LUX9612 ML3729R ML6413 ML6411 ML7667 ML7689 XHT1171 XHT2141 MPX1

XHT3143 XHT3146 XHT4141 XHT4143

Product Description: Poly (bisphenol-A-carbonate) [CASRN 111211-39-3 or 103598-77-

2] Sheet

Product Type: Commercial Product

Recommended use: May be used as received, processed or thermoformed to produce

other articles, or as a component of other industrial products.

Company: SABIC Innovative Plastics

One Plastics Avenue Pittsfield, MA 01201 USA

(413) 448-5400 www.sabic-ip.com

Emergency Telephone Number: 800/447-4545

Emergency Transportation/CHEMTREC (24 HOUR) 800/424-9300

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous.

Product Name: **LEXAN MSDS** Page 1 of 7 Revision date: 14-Apr-2016

### 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

- · Plastic film or sheet
- Can burn in a fire creating dense toxic smoke.
- Molten plastic can cause severe thermal burns.
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

HMIS Rating	Health: 0	Flammability: 1	Reactivity: 0	
Skin co	ntact:	Not likely	to cause irritation.	
Eye Cor	ntact:	Resin par to eyes.	ticles, like other inert materials, are mechanically irritating	
Inhalatio	on:	Inhalation	unlikely due to physical form.	
Ingestion:		Ingestion	Ingestion not likely due to physical form.	
Chronic Inform	mation			
Resin Is	ssues:	respirator headache condensa	g fumes may cause irritation to the eyes, skin, and y tract. In cases of severe exposure, nausea and can also occur. Grease-like processing fume tes on ventilation ductwork, molds, and other surfaces e irritation and injury to skin.	
Aggrava	ated Medical Conditions:	aggravate individuals	RESTRICTIONS: There are no known health effects d by exposure to this product. However, certain sensitives and individuals with respiratory impairments may be y exposure to components in the processing vapors	
		4. FIRST AID MEAS	URES	
Inhalatio	on:	be hazard or fumes,	ic treatment is necessary since this material is not likely to lous by inhalation. If exposed to excessive levels of dusts remove to fresh air and get medica attention if cough or ptoms develop.	
Skin Contact:		irritation o immerse i to dissipa	n water and soap as a precaution. Get medical attention if levelops or persists. For hot product, immediately in or flush affected area with large amounts of cold water te heat. Cover with clean cotton sheeting or gauze and of medical attention.	
Eye Cor	ntact:	any conta	ely flush with plenty of water. After initial flushing, remove ct lenses and continue flushing for at least 15 minutes. If on persists, consult a specialist.	
Ingestic	on:	No hazaro	ds which require special first aid measures.	
Precaut	ions:	tract. If s	g fumes inhalation may be irritating to the respiratory ymptoms are experienced remove victim from the source ination or move victim to fresh air and obtain medical	

## **5. FIRE-FIGHTING MEASURES**

Explosive Limits			
upper: lower:	Not applicable Not applicable		
Suitable Extinguishing Media:	Water spray mist or foam.		
Extinguishing media which must not be used for safety reasons:	Carbon dioxide and dry chemical are not recommended because their lack of cooling capacity may permit re-ignition.		
Hazards from Combustion Products:	Fire will produce dense black smoke containing hazardous combustion products, carbon oxides, hydrocarbon fragments		
Special Protective Equipment for Firefighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Figh fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.		
Specific Hazards:	Take precautionary measures against static discharges. Thermal decomposition can lead to release of irritating gases and vapors. Dust formed by operations such as cutting or grinding may form ar explosive mixture in air.		
6. ACCIDENTAL R	ELEASE MEASURES		
Clean up:	Gather and store in a closed container pending a recyclability or waste disposal evaluation.		
Personal Precautions:	See section 8.		
Environmental Precautions:	Do not flush into surface water or sanitary sewer system. Should not be released into the environment.		
7. HANDLING AND STORAGE			
Handling:	Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. Accumulation of waste films, sheets and/or masking may create a slipping hazard.		

Keep away from heat and sources of ignition.

Storage:

Product Name: **LEXAN MSDS** Page 3 of 7 Revision date: 14-Apr-2016

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures to Reduce Exposure: Handle in accordance with good industrial hygiene and safety

practice. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other

surfaces using appropriate personal protection.

Hand Protection: Protective gloves

Eye Protection: Safety glasses

Respiratory Protection: When using this product at elevated temperatures, implement

engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid gases and particulate matter) if processing fumes are not adequately controlled or operators experience symptoms of overexposure. If dust of powder are produced from secondary operations such as sawing or grinding,

use a respirator approved for protection from dust.

Skin and Body Protection: Long sleeved clothing

**Hygiene Measures:** When using, do not eat, drink or smoke.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid

Appearance:Sheet or filmColor:VariousOdor:None or slight

Melting point/range: This product does not exhibit a sharp melting point but softens

gradually over a wide range of temperatures.

**Explosive Limits** 

upper:Not applicablelower:Not applicable

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions. Hazardous polymerization does not

occur.

Conditions to Avoid: Do not exceed melt temperature recommendations in product

literature.

Hazardous Decomposition Products: Processing fumes evolved at recommended processing conditions

may include trace levels of hydrocarbon fragments, phenol,

alkylphenols, diarylcarbonates.

### 11. TOXICOLOGICAL INFORMATION

# Acute Toxicity: LD50/oral/rat: >5000 mg/kg, estimated

LD50/dermal/rabbit: >2000 mg/kg, estimated

Inhalation: Inhalation unlikely due to physical form.

Eye Contact: Resin particles, like other inert materials, are mechanically irritating

to eyes.

Skin contact: Not likely to cause irritation.

**Ingestion:** Ingestion not likely due to physical form.

Chronic Toxicity: No information available

IARC:Not ListedOSHA:Not regulatedNTP:Not tested

Remarks: The toxicological data has been taken from products of similar

composition

**Special Studies:** Processing fumes from similar products are not considered toxic.

In acute inhalation tests, laboratory rats were exposed to processing fumes at concentrations exaggerating those that would likely occur in workplace situations. No deaths or signs of toxicity, except transient irritancy in some cases, were noted during the 6 hour fume exposure tests. There were no distinct or consistent treatment related tissue or organ changes noted in gross

necropsies.

### 12. ECOLOGICAL INFORMATION

Other information: Ecological damages are not known or expected under

normal use.

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal: Recycling is encouraged. Landfill or incinerate in accordance with

federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine

waste classification.

US EPA Waste number: None

# Transport Classification: Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines. DOT ADR/RID/ADNR IMDG ICAO IATA-DGR

### 15. REGULATORY INFORMATION

### **International Inventories:**

**MEXICO** 

These film and sheet products are considered articles and thus exempt from inventory listing.

### CERCLA/SARA 311/312/313:

This product is a non-hazardous article and therefore not subject to the requirements of Title III of SARA (Emergency Planning and Community Right-To-Know Act).

### Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### WHMIS hazard class:

Non-controlled

### California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

### RoHS EU Directive 2002/95/EC:

This product complies with RoHS - it does not intentionally contain banned chemicals.

### **16. OTHER INFORMATION**

LEXAN\* Sheet is a registered trademark of SABIC Innovative Plastics

Prepared by: Product Stewardship & Toxicology

DISCLAIMER: This Material Safety Data Sheet [MSDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this MSDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this MSDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This MSDS is based on information, that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

**End of Material Safety Data Sheet**